

FEATURES

- 5.03 mm X 3.89 mm active area
- Low dark current
- Long term stability
- Light detection 483-493 nm

DESCRIPTION

19.57 mm² Low Dark Current Photodiode with P on N construction. Hermetically packaged in an isolated case TO-5 with a clear borosilicate glass window cap and internal 488 nm, 10 nm FWHM, 70% transmission bandpass filter. The internal filter is also available with alternate bandwidth and transmission values.

APPLICATIONS


- Precision photometry
- Analytical instruments
- Medical equipment
- Liquid chromatography




ABSOLUTE MAXIMUM RATING

SYMBOL	PARAMETER	MIN	MAX	UNITS
T _{STG}	Storage Temp	-30	+70	°C
T _{OP}	Operating Temp	-25	+70	°C
V _{R(OP)}	Reverse Operating Voltage	-	50	V
I _{I(PEAK)}	Peak DC Current	-	10	mA

SCHEMATIC



SPECTRAL RESPONSE



ELECTRO-OPTICAL CHARACTERISTICS @ 22° C

SYMBOL	CHARACTERISTIC	TEST CONDITIONS	MIN	TYP	MAX	UNITS
R _{SH}	Shunt Resistance	V _R = ±10 mV	100	200	---	MΩ
I _D	Dark Current	V _R = 5 V	---	0.35	---	nA
C	Capacitance	V _R = 0 V	---	160	---	pF
		V _R = 5 V	---	50	---	
	Responsivity	V _R = 0 V; λ = 488 nm	---	0.19	---	A/W
NEP	Noise Equivalent Power	V _R = 5 V; λ = 488 nm; R _L = 50 Ω	---	5.9 X 10 ⁻¹⁴	---	W/Hz ^{1/2}
V _{BR}	Breakdown Voltage	I _R = 10 μA	50	---	---	V
t _r	Rise Time	V _R = 5 V; λ = 488 nm; R _L = 50 Ω	---	30	---	ns

Disclaimer: Due to our policy of continued development, specifications are subject to change without notice.

USA:

Pacific Silicon Sensor, Inc.
 5700 Corsa Avenue, #105
 Westlake Village, CA 91362 USA
 Phone (818) 706-3400
 Fax (818) 889-7053
 Email: sales@pacific-sensor.com
www.pacific-sensor.com

7/21/2010

International sales:

Silicon Sensor International AG
 Peter-Behrens-Str. 15
 D-12459 Berlin, Germany
 Phone +49 (0)30-63 99 23 10
 Fax +49 (0)30-63 99 23 33
 Email: sales@silicon-sensor.de
www.silicon-sensor.de