

Features

- 33 mm² PIN detector
- High sensitivity
- High shunt resistance
- UV/blue enhanced

Description

UV-blue enhanced square active area PIN photodiode with 33 mm² active area. Metal can type hermetic TO8 package with UV clear glass window.

Application

- UV exposure meters
- Pollution monitoring
- Medical equipment
- Fluorescence detector

RoHS


2002/95/EC




Absolute maximum ratings

Symbol	Parameter	Min	Max	Unit
T _{STG}	Storage temp	-55	125	°C
T _{OP}	Operating temp	-40	100	°C
V _{max}	Max reverse voltage		20	V
I _{PEAK}	Peak DC current		10	mA

Spectral response (23 °C)



Schematic



Electro-optical characteristics @ 23 °C

Symbol	Characteristic	Test Condition	Min	Typ	Max	Unit
	Active area		5694 x 5694			µm
	Active area		33			mm ²
I _D	Dark current	V _R = 5 V		2		nA
C	Capacitance	V _R = 0 V		1200		pF
		V _R = 5 V		400		pF
	Responsivity	λ = 340 nm		0.22		A/W
		λ = 900 nm		0.47		A/W
t _R	Rise time	V _R = 5 V; λ = 410 nm; R _L = 50 Ω		800		ns
	Shunt Resistance	V _R = 10 mV	30	100		MΩ
	N.E.P.	V _R = 10 V		2 E-14		W/√Hz
V _{BR}	Breakdown voltage	I _R = 2 µA	30	50		V

European, International Sales:



International AG


Silicon Sensor International AG
 Peter-Behrens-Strasse 15
 12459 Berlin
 Germany
 Phone: +49-30-6399-2399
 Fax: +49-30-6399-23752
 E-Mail: sales@silicon-sensor.com

USA:




Pacific Silicon Sensor, Inc.
 5700 Corsa Avenue #105
 Westlake Village
 CA 91362 USA
 Phone: +1-818-706-3400
 Fax: +1-818-889-7053
 E-Mail: sales@pacific-sensor.com


Quantum efficiency (23 °C)



Capacitance as fct of reverse bias (23 °C)



Dark current as fct of bias (23 °C)



Package dimension:

Small quantities: Foam pad, boxed (12 cm x 16.5 cm)

Handling:

Please refer to document "Instructions for handling and processing"

Disclaimer: Due to our strive for continuous improvement, specifications are subject to change within our PCN policy according to JESD46C.

European, International Sales:



International AG

Silicon Sensor International AG
 Peter-Behrens-Strasse 15
 12459 Berlin
 Germany
 Phone: +49-30-6399-2399
 Fax: +49-30-6399-23752
 E-Mail: sales@silicon-sensor.com

USA:



Pacific Silicon Sensor, Inc.
 5700 Corsa Avenue #105
 Westlake Village
 CA 91362 USA
 Phone: +1-818-706-3400
 Fax: +1-818-889-7053
 E-Mail: sales@pacific-sensor.com